

COMPUTING GATEWAYS

FEATURE / INTERFACE COMPARISON

Features / Interface	Order number	Galvanic Isolation	FlexRay A/B	CAN (total)	thereoff CAN FD capable	thereoff CAN low-speed capable	LIN	EtherCAT (Slave)	Analog in	Analog out	Digital in/out	Ethernet 10/100 Base-T	Automotive Ethernet 100/1000 Base-T1	USB 2.0 device	USB 2.0 host	SDHC slot	Prot. class
CANnector																	
S	1.01.0091.00000	✓	-	6	2	-	2	-	-	-	2	1	-	1	2	-	IP40
L	1.01.0091.00010	✓	-	8	4	-	2	-	-	-	2	1	-	1	2	-	IP40
SE	1.01.0091.00100	✓	-	6	2	-	2	1	-	-	2	1	-	1	2	-	IP40
LE	1.01.0091.00110	✓	-	8	4	-	2	1	-	-	2	1	-	1	2	-	IP40
FRC-EP190																	
Plus CANonly	1.13.0094.10107	✓	-	8	4	2	2	-	2	-	4	1	-	1	1	1	IP42
FlexRay Plus 4	1.13.0094.10507	✓	1	8	4	2	2	-	-	-	4	1	-	1	1	1	IP42
Max EtherCAT	1.13.0094.10407	✓	1	8	4	2	2	1	-	-	4	1	-	1	1	1	IP42
FRC-EP170																	
	1.13.0142.00002	-	1	4	-	1	1	-	-	-	4	1	-	1	1	1	IP42
CANonly	1.13.0142.01002	-	-	4	-	1	1	-	-	-	4	1	-	1	1	1	IP42
Plus CANonly	1.13.0142.01302	-	-	6	2	1	1	-	-	-	4	1	-	1	1	1	IP42
Plus	1.13.0142.00302	-	1	6	2	1	1	-	-	-	4	1	-	1	1	1	IP42
MOBILIZER																	
Standard 800	1.01.0143.08000	✓	-	8	8	-	2	-	-	-	2	1	-	1	2	1	IP40
Pro 820 EtherCAT	1.01.0143.08201	✓	-	8	8	-	2	1	4	2	6	1	1	1	2	1	IP40
Pro 822 EtherCAT	1.01.0143.08221	✓	1	8	8	-	2	1	4	2	6	1	1	1	2	1	IP40