

## Ixxat FRC-EP170

Item number: 1.13.0142.00002

The Ixxat FRC-EP170 is an advanced solution for automotive engineering that integrates multiple bus systems. It features four CAN channels, one of which is CAN low-speed capable, including FlexRay, LIN and Digital in/out functionalities. This makes it an ideal solution for logging, gateway, and residual bus simulation applications. Configuration is easily done with the Ixxat Advanced Configuration Tool (ACT).



*Configurable automotive platform (1x FlexRay, 4x CAN)*

## Features and benefits

### ✓ Go-to solution for demanding network requirements

Enables easy integration of multiple bus systems into a single, compact device. This is essential for e-mobility projects and complex industrial applications.

### ✓ Multi-connectivity with various interfaces

Additional interfaces included: 1 x FlexRay, 1 x LIN, 1 x Ethernet (10/100 Base-T), 4 x Digital in/out (A/D), USB 2.0 device and host and a SDHC slot. Further extension options are available.

### ✓ Embedded platform with own processing power

All applications run on the device, a PC is only needed for configuration or stimulation/visualization of data, as the actual intelligence is outsourced to the embedded platform.

### ✓ Quick and easy configuration through ACT support

The FRC-EP series is supported by the Ixxat ACT (Advanced Configuration Tool), a Windows-based tool to easily configure the device via drag and drop. Most use cases can be solved by using ACT Freeware.

### ✓ Extensive CAN connectivity

The FRC-EP170 features four CAN channels, thereof one CAN low-speed capable, catering extensive connectivity for a wide range of automotive applications.

### ✓ Improved data management for efficient engineering

Streamlines data management and protocol handling, optimized for automotive testing, logging and gateway operations. Ensuring easy integration and reliable performance.

### ✓ Overvoltage protection

Galvanic isolation safeguards against overvoltage and protects from potential electrical damage.



## General

Net Width (mm)	113
Net Height (mm)	142
Net Depth (mm)	40
Net Weight (g)	940
Packed Weight (g)	940
Operating Temperature °C Min	-40
Operating Temperature °C Max	80
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	10 to 95 %, non-condensing
Current Consumption Type Value at Vcc Nom (mA)	320 mA (12 V DC)
Input Voltage (V)	6 V to 36 V DC
Power Connector	3-pole
Configuration	The Ixxat FRC-EP170 is a Linux platform that is able to work standalone without any connected PC. For the standalone function a configuration is needed, that can be created and downloaded to the device via the PC based Ixxat Automotive Configuration Tool (ACT) and an USB connection.
Content of Delivery	FRC-EP170 device, user manual, power supply cable (2 m, 3-pin Binder socket to 3 x 4 mm banana plugs), USB 2.0 cable (2 m, Type A to Mini Type B), runtime licences for Gateway and RBS, available as download: Advanced Configuration Tool (ACT)
Mounting	Panel mount
Housing Materials	Aluminium
Packaging Material	Cardboard

## Identification and Status

Product ID	1.13.0142.00002
------------	-----------------



## Identification and Status

Successor	1.13.0094.10107,1.13.0094.10507,1.13.0094.10407
Country of Origin	Germany
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	EAR99

## Physical Features

Connectors / Input / Output	1 x RJ45 connector (Ethernet), 1 x USB type B port, 1 x USB type A port, 1 x SD card slot, 1 x 7-pin Binder female panel mount connector (remote/debug), 1 x 3-pin Binder male panel mount connector (power), 1 x D-Sub HD15 male connector, 1 x D-Sub HD15 female connector, 1 x RP-SMA female connector (WiFi/antenna)
Contains Battery	No

## CAN Features

CAN Mode	CAN high-speed (ISO 11898-2), CAN low-speed (ISO 11898-3)
CAN Transceiver	TI SN65HVD251

## CAN FD Features

CAN FD Transceiver	TCAN334GDCN
--------------------	-------------

## LIN Features

LIN Transceiver	TJA1020
-----------------	---------

## Certifications and Standards

Protection Class IP	IP42
ETIM Classification	EC001604
CE	Yes
TELEC	No
WEEE Category	IT and telecommunications equipment



Use Case

